

MAGNUM

SPECIFICATIONS

• Gaseous Generator:

MGG210

- o Fuel: Natural Gas, LP or Wellhead Gas
- o 277/480VAC, 3 phase, 4 wire, 60 Hz, 1800RPM
- o Prime Power 182kW/228kVA (273 output amps)
- o 125 degree C Prime Power rated
- Standard Features:
 - o PSI Engine
 - o NG D111TIC 11.1L, 4-cycle, 6-cylinder, turbocharged, charge air cooled Engine
 - o UCI274G-311, 277/480V 12 lead PMG Alternator
 - o Tandem Axle Oil Field Trailer #7000 Axles, electric brake, 3" Pintle
 - o InteliGen Controller Unit to Unit paralleling feature set
 - o 300AT, 80% rated Thermal Magnetic Line Circuit Breaker
 - o Skid-mounted in heavy-gauge aluminum sound attenuated enclosure
 - o Dual Stage Air Cleaner
 - o Critical Grade Silencer with Flex Connection
 - o Coolant & Oil Drains Plumbed to skid base, w/ shutoff valves
 - o 16 gallon Ren Oil makeup unit
 - o Auto change over Nat. gas to L.P. Liquid
 - o Battery Disconnect Switch
 - o Panel Light
 - o Buck Transformer w/120VAC outlet receptacles
 - o Starting Batteries, Rack and Cables
- 1 Year/2,000 Hour Prime Power Warranty
- EPA Certified