

Model 6918-0 (49ST/Canada)

UPC: 696471069181

1 of 2



FEATURES

- EASY PRIME™ Funnel design for quick and easy priming
- Powerful Generac Pump - Can pump up to 158 gallons per minute
- Color coded suction and discharge ports to ensure the correct hose connections
- Durable design - Silicon Carbide Seal, Cast Iron Volute and Impeller
- Generac 208cc OHV engine with splash lubrication provides a long engine life

Specifications

Engine Type	4 cycle/OHV
Engine Displacement (cc)	208
Start Type	Recoil Pull Start
Low Oil Shutdown Method	Low Level
Recommended Oil	10W-30 / SAE30
Fuel Capacity (gal/l)	0.95/3.6
Max Run Time	2.0 hrs
Flow gpm/lpm	158/598
Max Total Head (ft/m)	108/32.9
Max Suction Lift (ft/m)	26/7.9
Mechanical Seal Type	Silicon Carbide
Solid Handling (in)	N/A
Suction Port (NPT)	2.0
Discharge Port (NPT)	2.0
Pump Housing	Aluminum
Impeller	Cast Iron
Volute	Cast Iron

Hose Kit Included	N/A
Discharge Hose Length (ft/m)	N/A
Suction Hose Length (ft/m)	N/A
Hose Connections	N/A
Strainer	N/A
Wheel Kit	N/A
Country of Origin	China
Warranty	1 Year
Manual Part #	0K9077
Length (L) (in/mm)	19.0/482
Width (W) (in/mm)	15.2/387
Height (H) (in/mm)	17.0/431
Unit Weight (lbs/kg)	53.6/24.3
Carton Length (in/mm)	19.7/499
Carton Width (in/mm)	15.8/402
Carton Height (in/mm)	17.8/453
Shipping Weight (lbs/kg)	58.4/26.5

